

## **BOYLE COUNTY FLOODPLAIN DEVELOPMENT PERMIT**

**PERMIT NUMBER:** \_\_\_\_\_

**NAME OF PERMITTEE:** \_\_\_\_\_

**ADDRESS OF PERMITTEE:** \_\_\_\_\_  
\_\_\_\_\_

The above named permittee applied for a development permit on \_\_\_\_\_. The application has been reviewed by the local floodplain administrator and it has been determined that the proposed development is located within an identified floodplain in a Zone \_\_\_\_\_. The proposed development occurs on FIRM/FHBM panel \_\_\_\_\_ dated \_\_\_\_\_.

The administrator has reviewed the plans and specifications of the proposed development for conformance with the development standards required by Boyle County's Flood Damage Prevention Ordinance. The permittee is hereby authorized to proceed with the work described in the permit application at the proposed location.

To maintain compliance with the development standards of Boyle County's Flood Damage Prevention Ordinance and to eliminate or minimize flood damage potential to the proposed development, the permittee is hereby directed to construct the proposed development in accordance with the following special provisions:

- ( ) A state stream construction permit must be obtained from the Kentucky Division of Water, Floodplain Management Section, stating the Base Flood Elevation (BFE), or elevation in Mean Sea Level (MSL), to which the lowest floor of a structure must be elevated or floodproofed.
- ( ) For residential structures, the lowest floor (including basement) must be elevated to \_\_\_\_\_ feet Mean Sea Level (MSL), according to Boyle County's Flood Damage Prevention Ordinance.
- ( ) For non-residential structures, the lowest floor (including basement) must be elevated or floodproofed to \_\_\_\_\_ feet Mean Sea Level (MSL), according to Boyle County's Flood Damage Prevention Ordinance.
- ( ) Permittee must submit a certification from a registered professional engineer, architect, or land surveyor that the lowest floor of the residential structure has been constructed at the specified elevation.

- ( ) For non-residential floodproofing, a floodproofing certificate is required by a registered professional engineer or architect. Signature certifies that the floodproofing methods are adequate to withstand the flood depths, pressures, velocities, impact, and uplift forces and other factors associated with the base flood.
- ( ) The foundation of the structure must, as a minimum, comply with the Flood Damage Prevention Ordinance stipulations.
- ( ) The materials used to build the structure, which are below the BFE, are flood resistant.
- ( ) The foundation walls below the BFE must be vented to allow for the free flow of floodwaters. Total vent area must equal or exceed one square inch of opening per square foot of floor space, with the bottom of the vents no greater than one foot above the finished adjacent grade (garage doors without openings specifically designed to allow for the free flow of floodwaters do not meet the openings requirement).
- ( ) The water supply inlet and sanitary sewage outlet must have an automatic backwater or back flow valve device installed.
- ( ) Other provisions.
- ( ) Copy of Flood damage Prevention Ordinance is attached.

---

**ACKNOWLEDGEMENT OF CONDITIONS  
BY PERMITTEE**

**DATE**

---

**SIGNATURE OF LOCAL FLOODPLAIN  
ADMINISTRATOR**

**DATE**